

SPECIFICATIONS

<p>Dimensions : 205 x 67 cm Weight : ±77 kg Height adjustment : 50 – 100 cm electric 52 – 99 cm hydraulic Lifting capacity: Max. 200kg Mains voltage: 230 VAC, 50/60 Hz 120 VAC, 60 Hz 100 VAC, 50/60 Hz Power consumption: Max. 2.0 A Insulation: Class II Device Classification: I Applied parts: Type BF Humidity proof: IP21</p>	<p>Motor force: 6 kN Motor usage: Max. 2 minutes on / 18 minutes off Hydraulic pump: 10kN Frame material: Steel frames Frame finish: Powder coated white RAL 9016 Conformity: IEC/EN 60601-1 IEC/EN 60601-1-2 EC directives 2017/745 (MDR) 2012/19/EC 2011/65/EU</p> <p style="font-size: 2em; font-weight: bold;">CE</p> <p>Warranty: Table 3 years, Classique upholstery, 1 year</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CUSHION UPHOLSTERY

Classique: PVC, phthalate free, biocompatible, abrasion resistant and flame retardant.

CUSHIONS FINISH

Linear: Single padded, 40 kg/m³

OPTIONS

Wheels
 Safety switch for foot- or hand control

Face opening
 Ergomax face opening

DIMENSIONS / FUNCTIONALITY

