

SPECIFICATIONS

Dimensions :	205 x 67 cm	Motor force:	6 kN
Weight :	±79 kg	Motor usage:	Max. 2 minutes on / 18 minutes off
Height adjustment :	50 – 100 cm electric 52 – 99 cm hydraulic	Hydraulic pump:	10kN
Lifting capacity:	Max. 200kg	Frame material:	Steel frames
Mains voltage:	230 VAC, 50/60 Hz 120 VAC, 60 Hz 100 VAC, 50/60 Hz	Frame finish:	Powder coated white RAL 9016
Power consumption:	Max. 2.0 A	Conformity:	IEC/EN 60601-1 IEC/EN 60601-1-2 EC directives 2017/745 (MDR) 2012/19/EC 2011/65/EU
Insulation:	Class II	CE	Warranty: Table 3 years, Classique upholstery, 1 year
Device Classification:	I		
Applied parts:	Type BF		
Humidity proof:	IP21		

CUSHION UPHOLSTERY

Classique: PVC, phthalate free, biocompatible, abrasion resistant and flame retardant.

CUSHIONS FINISH

Linear: Single padded, 40 kg/m³

OPTIONS

Wheels
Safety switch for foot- or hand control

Face opening
Ergomax face opening

DIMENSIONS / FUNCTIONALITY

